

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Place the Wall plate(6) over the Outbox(1) .Mark the location of keyhole slots on the wall,remove the Wall plate(6).
2. Drill a 1/4" hole at the on the wall,Carefully hammer a Wall anchor(12) into the wall.
3. Replace the Wall plate(6) over the OutBox(1) with the Mounting screw(10).Feed the Anchor screw(11) through the keyhole and thread into the Wall anchor(12).
4. Pull out the outlet wire and ground wire from the Outlet box(1).Make wire connections
 - Ribbed wire(w/o marking) from light to White wire(2) from power source.
 - Smooth wire(w/o marking) from light to Black wire(3) from power source.
 - Loop the Ground wire(4) to Mounting bar(6) with a Green screw(9)
5. Attach the Back plate(15) against the Wall plate(6),secure with the Ball nut(14)
6. Put the Glass(17) through Socket(16),then secure by Socket ring(18)
7. Install bulbs:(bulbs not include)
(Please don't exceed the maximum capacity that recommended on the sockets).

INSTALLATION IS NOW COMPLETED

