



Features

- Durable cast zinc-magnesium faceplate with powder coated finish (plated for Stainless Steel)
- Pair light modules with a multitude of faceplate options for customized low level lighting
- Light module rated for wet locations (IP65)
- No rough-in kit required - mounts to standard depth single gang junction box (includes watertight gasket)
- 7" 18AWG lead wires
- cETLus Listed for indoor and outdoor use
- 50,000 hours rated life

Available Finishes



White



Stainless Steel



Dark Bronze

Listing / Ratings



SGL3

Available in 120-277V warm white light. No rough-in box required, these indoor/outdoor LED step lights are easy to install for stair safety and visibility. Use to light corridors, stairs, landings, decks and perimeter/landscape areas.

Technical Information

Series	SGL3
Input Voltage	120-277V AC, 60Hz
CCT	3000K
CRI	82+
Wattage	1.7W per module
Lumens	See individual product
Beam Angle	Varies by faceplate
Dimmable	N/A
Dimensions	2-3/4"W x 4-1/2"H x 1-1/2"D (light module) 2-15/16"W x 4-3/4"H x 3/8"D (faceplates)
Mounting	Wall mount (standard single gang junction box)
Rating	cETLus Listed (wet location)
Rated Life	50,000 hrs

SGL3 Light Modules



120-277V Warm White LED Module
SGL3-LED-WW (100-277V / 1.7W / 3000K)

SGL3 Faceplates



Smooth Lens
SGL-SM-DB (Dark Bronze, 79Lm)
SGL-SM-SS (Stainless Steel, 80Lm)
SGL-SM-WH (White, 81Lm)



Horizontal Louver
SGL-HL-DB (Dark Bronze, 16Lm)
SGL-HL-SS (Stainless Steel, 30Lm)
SGL-HL-WH (White, 40Lm)



Horizontal Wave
SGL-HW-DB (Dark Bronze, 39Lm)
SGL-HW-SS (Stainless Steel, 71Lm)
 Limited Quantities Available



Vertical Scoop
SGL-VS-SS (Stainless Steel, 25Lm)
 Limited Quantities Available

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

ARCHITECTURAL LIGHTING

POWER SUPPLIES

SGL3